


Profilati metallici

Tubi (scatolati) in Acciaio a sezione rettangolare



b x a mm	s mm	Peso kg/m	Sezione metallica cm ²	Momento di inerzia		Modulo di resistenza		Raggio di inerzia	
				Jx cm ⁴	Jy cm ⁴	Wx cm ³	Wy cm ³	ix cm	iy cm
20 x 10	1.5	0.636	0.810	0.380	0.118	0.380	0.236	0.685	0.382
25 x 10	1,5	0,754	0,960	0,681	0,145	0,545	0,290	0,842	0,389
	2,0	0,973	1,240	0,839	0,170	0,671	0,340	0,823	0,370
30 x 10	1,5	0,871	1,110	1,100	0,173	0,733	0,364	0,995	0,395
	2,0	1,130	1,440	1,370	0,203	0,913	0,406	0,975	0,375
30 x 15	1,5	0,989	1,260	1,410	0,455	0,938	0,607	1,060	0,601
	2,0	1,290	1,640	1,760	0,556	1,170	0,741	1,040	0,582
30 x 20	1,5	1,110	1,410	1,710	0,894	1,140	0,894	1,100	0,796
	2,0	1,440	1,840	2,160	1,110	1,440	1,110	1,080	0,778
40 x 20	2,0	1,760	2,240	4,450	1,440	2,220	1,440	1,410	0,802
	3,0	2,540	3,240	6,080	1,890	3,040	1,890	1,370	0,764
40 x 30	2,0	2,070	2,640	5,890	3,730	2,940	2,480	1,490	1,190
	3,0	3,010	3,840	8,140	5,080	4,070	3,390	1,450	1,150
50 x 20	2,0	2,070	2,640	7,850	1,760	3,140	1,760	1,720	0,816
	3,0	3,010	3,840	10,90	2,330	4,360	2,330	1,680	0,779
50 x 25	2,0	2,230	2,840	9,010	2,960	3,600	2,370	1,780	1,020
	3,0	3,250	4,140	12,60	3,990	5,020	3,190	1,740	0,982
50 x 30	2,0	2,390	3,040	10,20	4,510	4,060	3,010	1,830	1,220
	3,0	3,490	4,440	14,20	6,180	5,680	4,120	1,790	1,180
60 x 20	2,0	2,390	3,040	12,60	2,090	4,200	2,090	2,030	0,829
	3,0	3,490	4,440	17,60	2,760	5,870	2,760	1,990	0,788
60 x 30	2,0	2,700	3,440	16,00	5,300	5,320	3,530	2,150	1,240
	3,0	3,960	5,040	22,50	7,280	7,500	4,850	2,110	1,200
b x a	s	Peso	Sezione	Momento di inerzia		Modulo di resistenza		Raggio di inerzia	

mm	mm	kg/m	metallica cm2	Jx cm4	Jy cm4	Wx cm3	Wy cm3	ix cm	iy cm
60 x 40	2,0	3,010	3,840	19,30	10,20	6,430	5,110	2,240	1,630
	3,0	4,430	5,640	27,40	14,30	9,120	7,150	2,200	1,590
80 x 20	2,0	3,010	3,840	26,80	2,740	6,700	2,740	2,640	0,845
	3,0	4,430	5,640	38,10	3,640	9,510	3,640	2,600	0,803
80 x 30	2,0	3,330	4,240	32,90	6,870	8,220	4,580	2,790	1,270
	3,0	4,900	6,240	47,00	9,480	11,80	6,320	2,740	1,230
80 x 40	2,0	3,640	4,640	39,00	13,00	9,740	6,560	2,890	1,680
	3,0	5,370	6,840	55,80	18,40	14,00	9,210	2,850	1,640
80 x 60	2,0	4,270	5,440	51,10	34,80	12,80	11,60	3,060	2,530
	3,0	6,310	8,040	73,60	46,90	18,40	15,60	3,030	2,420
100 x 30	2,0	3,960	5,040	58,30	8,400	11,70	5,630	3,400	1,290
	3,0	5,840	7,440	83,90	11,80	16,80	7,870	3,360	1,260
	4,0	7,660	9,760	107,0	14,30	21,40	9,530	3,310	1,210
100 x 40	2,0	4,270	5,440	67,90	16,00	13,60	8,000	3,530	1,710
	3,0	6,310	8,040	98,00	22,50	19,60	11,30	3,490	1,670
	4,0	8,320	10,60	126,0	28,20	25,20	14,10	3,450	1,630
100 x 50	2,0	4,580	5,840	77,50	26,30	15,50	10,50	3,640	2,120
	3,0	6,780	8,640	112,0	37,70	22,40	15,10	3,600	2,090
	3,5	7,850	10,00	128,0	42,60	25,60	17,00	3,580	2,060
	4,0	8,950	11,40	144,0	47,40	28,80	18,90	3,560	2,040
120 x 40	2,0	4,900	6,240	108,0	18,90	18,00	9,450	4,160	1,740
	3,0	7,250	9,240	156,0	26,70	26,00	13,40	4,110	1,700
	4,0	9,580	12,20	201,0	33,40	33,50	16,70	4,060	1,650
120 x 60	2,0	5,530	7,040	136,0	46,20	22,70	15,40	4,400	2,560
	3,0	8,160	10,40	197,0	66,40	32,80	22,10	4,350	2,530
	3,5	9,500	12,10	227,0	75,80	37,80	25,30	4,330	2,500
	4,0	10,80	13,80	255,0	84,80	42,50	28,30	4,300	2,480
150 x 60	3,0	9,580	12,20	344,0	81,00	45,80	27,00	5,300	2,570
	4,0	12,70	16,20	447,0	104,0	59,60	34,50	5,260	2,530
	5,0	15,70	20,00	544,0	124,0	72,60	41,40	5,220	2,490
150 x 80	3,0	10,50	13,40	409,0	154,0	54,50	38,50	5,520	3,390
	4,0	14,00	17,80	532,0	198,0	70,90	49,50	5,470	3,340
	5,0	17,30	22,00	649,0	240,0	86,50	60,00	5,430	3,300
150 x 100	3,0	11,50	14,60	473,0	253,0	63,10	50,60	5,690	4,160
	4,0	15,20	19,40	617,0	329,0	82,30	65,80	5,640	4,120
	5,0	18,80	24,00	754,0	400,0	101,0	80,00	5,610	4,080
180 x 90	3,0	12,40	15,80	686,0	234,0	76,20	52,00	6,590	3,850
	4,0	16,50	21,00	897,0	303,0	99,70	67,30	6,530	3,800
	5,0	20,40	26,00	1.099	368,0	122,0	81,80	6,500	3,760
200 x 100	3,0	13,80	17,60	947,0	324,0	94,70	64,80	7,330	4,280
	4,0	18,40	23,40	1.240	421,0	124,0	84,20	7,290	4,240
	5,0	22,80	29,00	1.522	512,0	152,0	102,0	7,240	4,200

b x a mm	s mm	Peso kg/m	Sezione metallica cm ²	Momento di inerzia		Modulo di resistenza		Raggio di inerzia	
				Jx cm ⁴	Jy cm ⁴	Wx cm ³	Wy cm ³	ix cm	iy cm
250 x 120	3,0	17,10	21,80	1.825	588,0	146,0	98,00	9,150	5,190
	4,0	22,80	29,00	2.397	767,0	192,0	128,0	9,090	5,140
	5,0	28,30	36,00	2.953	938,0	236,0	156,0	9,060	5,100
250 x 150	3,0	18,50	23,60	2.099	960,0	168,0	128,0	9,430	6,380
	4,0	24,60	31,40	2.760	1.257	221,0	168,0	9,380	6,330
	5,0	30,60	39,00	3.403	1.543	272,0	206,0	9,340	6,290
300 x 100	4,0	24,60	31,40	3.412	605,0	227,0	121,0	10,40	4,390
	5,0	30,60	39,00	4.208	738,0	281,0	148,0	10,40	4,350
	6,0	36,60	46,60	4.982	864,0	332,0	173,0	10,30	4,310